SMT078 | SMART BIDET TOILET

QUICK TECHNICAL DATASHEET / ENGLISH

ELECTRICAL & PERFORMANCE SPECIFICATIONS

Rated voltage	**220 V / 110 V AC**
Rated frequency	**50 Hz**
Rated power	**1450 W**
Maximum power	**1650 W**
Electric shock protection	**Category I**
Water supply	**Direct connection to supply pipe**
Dynamic inlet water pressure	**0.15 - 0.75 MPa (1.5 - 7.5 kgf/cm2)**
Rear wash water flow	**0.5 - 0.9 L/min**
Feminine wash water flow	**0.5 - 0.9 L/min**
Water heating	**Instantaneous / 1600 W**
Seat heating power	**50 W**
Warm-air drying power	**200 W**
Nominal water consumption	**<= 6.0 L**
Water-resistance rating	**IPX4**
Power cord length	**1.5 m**
Product weight	**40 kg**

TEMPERATURE ADJUSTMENT

Cleansing water	Approx. 34 / 37 / 40 C (low / medium / high)
Heated seat	Approx. 30 / 35 / 40 C (low / medium / high)
Warm-air dryer	Approx. 35 / 40 / 50 C (low / medium / high)

Source: supplied Little Whale English Installation & Use Manual, original technical table (page 12-13).
Original data values are retained. This sheet does not establish that the manual is certified for SMT078.
Confirm model compatibility, voltage variant and latest approved factory drawings before customer release.